

# PureWaterMachine™

by VERTEX

## Monitor Filter Life for Peace of Mind

*4 stage RO with Clean Tap Filter monitor measures clean water used and tells when to change filters.*

### Benefits

- Insure optimum filter performance
- Takes out chlorine taste and odors, dirt and sediment
- Comes ready to install, with instruction manual

### Standard Features

- Auto shut-off valve conserves water
- Long reach, non-airgap faucet
- Feed connection – threaded inlet adapter with metal ballvalve
- Drain clamp
- 1/4" flexible polyethylene tubing w/JACO compression fittings
- 2 year limited warranty

Use the VERTEX PureWaterMachine with a CleanTap™ filter monitor to insure that you are getting optimum filtration at all times. This electronic device measures the amount of water passing through the filters. A light indicator, green, yellow and red is installed on the clean water faucet. An electronic sensor module is connected to the tubing under the sink and measures the flow to the faucet. When the filter is good, the green light flashes when the faucet is on. When the filter has been used 80%, the yellow light flashes, and at 100%, it goes red. The CleanTap can be set at 500, 1000, or 3000 gallons. The CleanTap is also available as a kit to add to existing units. Battery operated.



### STAGE ONE

Sediment Filter, 5-Micron Polyspun Cartridge, 2 1/2" dia. x 9 3/4" long

### STAGE TWO

Activated Carbon Block Filter 5 Micron, 2 1/2" dia. x 9 3/4" long

### STAGE THREE

Reverse Osmosis Membrane, Filmtec 36 GPD TFC @ 65 PSI Pressure Differential

### STAGE FOUR

Post-Filter, In-Line, Granular Activated Carbon 2" dia. x 10" long

### TANK

4.0 Gallon Plastic Tank (metal tank available), Pre-pressurized with Butyl Bladder (2.5 gal. water capacity when full)

**Specifications:** Shipping Weight: 25 lb. Dimension: 14" L x 6" W x 18"H, Tank: 11 dia. x 15.5"H

**Conditions of Use:** Water must be microbiologically safe; System pressure, 40 min to 100 max psi; Temperature, 40 to 100° F; PH Range, 3 to 10; Turbidity – less than 1.0 NTU; TDS, 1500 PPM max

### ORDERING INFORMATION

<b>4 stage Reverse Osmosis with monitor</b>	PT-4.0/CT
<b>CleanTap Monitor kit only</b>	CTM-5005
<b>Air Gap Faucet option</b>	add /AG
<b>3/8" Line to Faucet option</b>	add /3/8
<b>Self-piercing Saddle Valve option</b>	add /SV
<b>Quick Connect Fittings option</b>	add /QC
<b>Metal Tank option</b>	add /MT
<b>Filter Replacement Kit</b>	FK-100

Authorized Dealer

